

GLOBE HOUSE, QUEENSWAY, ROCHDALE, OL11 2QY. T: 01706 655099. F: 01706 658712

TRIAD TRIAMEX







aesthetically pleasing perimeter fence suitable for most requirements. Efficient manufacturing processes ensure that Triamex Fencing is long lasting and affordable. The panels have square hollow section verticals set at a maximum 100mm gap, heavy-duty channel horizontal rails and are supported by rolled steel joist posts. Triamex Fencing is supplied Hot Dip Galvanised to BS EN ISO 1461 or Galvanised and Polyester Powder Coated. Standard heights are 1800mm, 2000mm, 2400mm and 3000mm and can be supplied with either square or angle tops. If undulating ground is a problem our special angle cleats allow the panels to be stepped on site and in particularly severe areas panels can be specially manufactured to suit the contour of the land. Domed headed bolts and permacone security nuts are supplied as standard to give additional security. Personnel and Vehicle entrance gates are also available to match all the Triamex Fencing range.



TRIAD Triamex

To complement our standard Triamex fencing, we offer four alternative designs. All have the same specification as our standard range, but each offer an additional feature.







GLOBE HOUSE, QUEENSWAY, ROCHDALE, OL11 2QY. T: 01706 655099. F: 01706 658712



TRIAD Triamex Elite An attractive and appealing fence, combining the strength of Triamex with a more traditional appearance



TRIAD Triamex Prestige Elite further enhanced by the addition of a box section post with feature top.



TRIAD Triamex Dart Triamex Dart is supplied with angle top rolled steel joist posts as standard and has a pressed steel spear to the top of each vertical.



TRIAD Triamex Deterrent Triamex Deterrent is supplied with angle top verticals as standard, and a crank to the top of each vertical which makes the fence even more intimidating to the would be intruder.

Standard heights: 1800, 2000, 2400 and 3000mm. Posts: 102x44 RSJ at 2750 post centres. Prestige: Box section posts. Centres and size of post dependent on fence height.

Vertical: 25x25 SHS set diamond to view to give a maximum gap of 100mm. Horizontal Rails: Heavy duty rolled steel channel. Up to 2400mm high - 2 (No), 3000mm high - 3 (No).

Fixings: Domed headed bolts, permacone security fixings and special angle cleats which allow the panels to be stepped 0-35mm and 85-123mm on site. Finish: Hot Dip Galvanised to BS EN ISO 1461 or Galvanised & Polyester



